


LED TECHNOLOGY

2800 sqm

Illuminated area



X-TRIPOD
T-ZERO_{PRO}

X-TRIPOD T-ZERO^{PRO}



FEATURES

- 4x 160W LED – illumination area 2800 sqm
- LED inclination and orientation - manual adjustment
- Max height 7 meters
- 4 section Manual Vertical mast with manual winch
- CEE Outlet socket present on the lighting tower
- 230V-50Hz connection
- Made in aluminium
- Stationary application
- Tripod structure with no.4 stabilizers retractable
- Easy to handle
- Transport Dimension: 640x370x1970 mm (LxWxH)
- Total weight 95 Kg
- Very compact for easily handling and transportability



Dimension & weight	Dimension min (mm)		Dimensions max (mm)		Total weight (kg)
	640x370x1970 (LxWxH)		2200x2200x7000 (LxWxH)		95
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated Area (sqm)
	LED	160W	4	65	2800
Mast	Lifting Method	Max Height	Max Wind Speed	Rotation	
	Manual	7,0 m	80 km/h	NO	
Input	Inlet plug				
	16A-230V				

The company reserves the right to modify the technical specifications, items and design without notice.
The images of the products are indicative for illustrative purposes only.